



Latitude Pro Arc Flash 10' Web SRL-P

*See chart for part numbers, hook configurations, and product weights

FEATURES :

- Complete confidence in full, continuous retraction with side payout housing.
- Reliable internal braking system eliminates need for external shock pack.
- 360/180° attachment point offers full range of motion.
- High strength semi-sealed assembly protects internal components from debris to extend product life.
- Translucent housing allows easy inspection of webbing, reserve line and pawl assembly.
- Trusted Kevlar® webbing and Nomex® flame-resistant label cover.
- Minimal exposed webbing protects against UV damage.
- Single leg and dual leg options available.
- Available with various hook and attachment options, see chart.
- All components are Z359.12 compliant.



Class

1

Anchor at or above dorsal D-ring

Product shown:
024-5486

USER WEIGHT CAPACITY

ANSI	130-310 lbs. (59-141 kg)
OSHA	Up to 420 lbs. (191 kg)

STANDARD COMPLIANT WITH

ANSI	Z359.14-2021
OSHA	1910.140, 1910.66
ASTM	F887

ANSI CLASS 1 (ABOVE D-RING)

Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.4 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 13 in. (33 cm)
Max. free fall distance	24 in. (61 cm)
Use below d-ring	NOT PERMITTED
Min. required fall clearance	4' 7" (1.4 m)
For full clearance requirements, see user instructions	

OSHA (BELOW D-RING)

Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 900 lbs. (408.2 kg)
Max. arrest distance	N/A
Actual arrest distance	≤ 58 in. (147 cm)
Max. free fall distance	24 in. (61 cm)
Use below d-ring	2 ft. (.06 m)
Min. required fall clearance	10' 3" (3.1 m)
For full clearance requirements, see user instructions	

MATERIAL SPECIFICATION

Webbing	20 mm Kevlar® webbing
Housing	Clear resin
Bracket	Steel, aluminum (dependent on configuration)
Hook options	Steel, aluminum, dielectric (dependent on configuration)



Latitude Pro Arc Flash 10' Web SRL-P



Standards: ANSI Z359.14-2021

OSHA 1910.140, 1910.66

ASTM F887

Capacity: ANSI 130-310 lbs. (59-141 kg)

OSHA Up to 420 lbs. (191kg)

CONNECTOR										ATTACHMENT																				
Part Number	Single Leg (S) / Dual Leg (D)		SRL Class	Working Length (ft.)	Lifeline Material	Lifeline Dimensions (in.)	Housing Material	Weight (lbs.)	LI Steel Swivel Snap Hook ①	Dielectric Snap Hook ②	Steel Tie Back Hook ③	LI Steel Swivel Rebar Hook ④	Steel Swivel Rebar Hook ⑤	Steel Swivel Rebar Hook ⑥	Steel Swivel Rebar Hook ⑦	Steel Swivel Rebar Hook ⑧	ALU Swivel Rebar Hook ⑨	ALU Swivel Rebar Hook ⑩	ALU Swivel Rebar Hook ⑪	ALU Swivel Rebar Hook ⑫	ALU Swivel Rebar Hook ⑬	ALU Swivel Rebar Hook ⑭	ALU Swivel Rebar Hook ⑮	ALU Swivel Rebar Hook ⑯	ALU Swivel Rebar Hook ⑰	ALU Swivel Rebar Hook ⑱	ALU Swivel Rebar Hook ⑲	ALU Swivel Rebar Hook ⑳	ALU Swivel Rebar Hook ㉑	
024-5482	1	S	10	Kevlar® Webbing	.7X.05	Clear Resin	3.3	X														X								
024-5483	1	S	10	Kevlar® Webbing	.7X.05	Clear Resin	3.0			X												X								
024-5484	1	S	10	Kevlar® Webbing	.7X.05	Clear Resin	4.0						X									X								
024-5485	1	S	10	Kevlar® Webbing	.7X.05	Clear Resin	3.8										X					X								
024-5486	1	S	10	Kevlar® Webbing	.7X.05	Clear Resin	3.3				X											X								
024-5487	1	S	10	Kevlar® Webbing	.7X.05	Clear Resin	3.1	X																						X
024-5488	1	S	10	Kevlar® Webbing	.7X.05	Clear Resin	2.8			X																				X
024-5489	1	S	10	Kevlar® Webbing	.7X.05	Clear Resin	3.9						X																	X
024-5490	1	S	10	Kevlar® Webbing	.7X.05	Clear Resin	3.7										X													X
024-5491	1	S	10	Kevlar® Webbing	.7X.05	Clear Resin	3.1				X																			X
024-5492	1	D	10	Kevlar® Webbing	.7X.05	Clear Resin	5.9	X																						X
024-5493	1	D	10	Kevlar® Webbing	.7X.05	Clear Resin	5.3			X																				X
024-5494	1	D	10	Kevlar® Webbing	.7X.05	Clear Resin	7.3						X																	X
024-5495	1	D	10	Kevlar® Webbing	.7X.05	Clear Resin	6.9										X													X
024-5496	1	D	10	Kevlar® Webbing	.7X.05	Clear Resin	5.9				X																			X
024-5497	1	D	10	Kevlar® Webbing	.7X.05	Clear Resin	6.0	X																						X
024-5498	1	D	10	Kevlar® Webbing	.7X.05	Clear Resin	5.4			X																				X
024-5499	1	D	10	Kevlar® Webbing	.7X.05	Clear Resin	7.4						X																	X
024-5500	1	D	10	Kevlar® Webbing	.7X.05	Clear Resin	7.0										X													X
024-5501	1	D	10	Kevlar® Webbing	.7X.05	Clear Resin	6.0				X																			X

