

ROOF ANCHORS BUILT FOR THE REAL WORLD

From permanent to reusable, Safewaze anchors are made to match the demands of modern roofing contractors. Whether you're working on standing seam, membrane, tile, corrugated or wooden structures, we have a solutions to protect your crew.





Peak Roof Anchor
020-4025

- Installs easily on roof peak
- Dual D-rings for access to both sides of peak
- Low profile, minimalistic design
- Constructed with durable stainless and zinc-plated steel



Permanent Roof Anchor
020-4026

- Installs easily between roof peak and eaves
- Low profile, minimalistic design
- Constructed with durable stainless and zinc-plated steel



Ridge Roof Anchor
020-4026

- Installs easily between roof peak and eaves
- Low profile, minimalistic design
- Constructed with durable stainless and zinc-plated steel



Reusable Roof Anchor
FS870
FS870N (includes nails)
FS870S (includes screws)

- Installed on peak or flat wood roof
- Hinged construction for adjustment to different angles



Knock Down Roof Anchor
FS871
FS871N (includes nails)

- Temporary, disposable design
- Installed on sloped or flat wood roofs



Chain Anchor
018-4000

- HLL compatible
- Installed on sloped or flat wood roofs





Standing Seam SRL Swivel Anchor
023-4095

- Swivel base fits most SRLs
- D-ring connection for energy absorbing lanyards
- HLL compatible
- Adjustable crossarm spans 24"-40" to fit different widths on both flat and pitched roofs



Standing Seam Swivel Anchor
023-4096

- D-ring connection for energy absorbing lanyards
- VLL compatible
- Adjustable crossarm spans 24"-40" to fit different widths on both flat and pitched roofs



Standing Seam Roof Anchor
FS-EX311

- Easy to install
- Accommodates a wide range of standing seams

TILE ROOFS



TileLink Anchor
022-4092 (Screws)
022-4094 (Rivets)

- Screws for install on wooden truss and rivets for install into metal truss
- Installs directly under tile
- Low profile design
- Built-in energy absorber reduces stress to structure

CORRUGATED ROOFS



Corrugated Roof Anchor
024-4112 (Steel)
024-4113 (Stainless Steel)

- Fasteners reinstall to maintain waterproofing
- Fits ridge heights up to 1-3/4" and widths up to 3-3/4"

MEMBRANE ROOFS



Membrane Roof Anchor
022-4090

- Drop-through design; no underside access
- Elevated eye bolt for abrasion prevention





225 Wilshire Avenue SW, Concord NC 28025



800-230-0319



safewaze.com

