



025-1632 through 025-1638

Contour Construction Harness: 3D, QC Chest, FD, TB Legs

FEATURES:

- More adjustability for a secure fit on a wide range of body types
- Ergonomic shoulder pad for balanced weight distribution
- Precise chest strap alignment for comfort and security
- Lightweight padding with superior airflow for all-day comfort
- Fixed dorsal D-ring
- Integrated SRL channel
- Quick-connect chest
- Front D-ring
- Side positioning D-rings
- Two mating buckle torso adjusters on each side
- Tongue buckle legs
- Breakaway lanyard keepers
- Floating waist pad for optimal positioning

FALL ARREST POINT(S):

- 1 Dorsal D-ring
- 1 Integrated SRL Channel

ITEM WEIGHT:

- 7.8 lbs. (3.5 kg)



DORSAL
ATTACHMENT



STERNAL
ATTACHMENT



WAIST
ATTACHMENT

USER WEIGHT CAPACITY

ANSI	130-310 lbs. (59-141 kg)
OSHA	Up to 420 lbs. (191 kg)

STANDARD COMPLIANT WITH

ANSI	Z359.11-2021
OSHA	1926.502, 1910.140

SIZE(S)

025-1632	X-Small
025-1633	Small
025-1634	Medium
025-1635	Large
025-1636	X-Large
025-1637	2X
025-1638	3X

COMPONENT

MATERIAL SPECIFICATION

Webbing	Polyester
D-ring (s)	Zinc-plated steel
Adjuster buckles	EP coated steel
Chest connection	EP coated steel
Leg connection	Zinc-plated steel buckle w/SS grommets
SRL channel	TPU, polycarbonate
Pads	Polyester, EVA, vinyl
Belt	Polyester, zinc-plated steel, SS grommets