



023-4105 Shuttle Anchor

FEATURES:

- Temporary or permanent anchor
- Raise SRLs, lanyards, and VLLs from the ground using black pull cord (100') and release them using red pull cord (50')
- Durable, reflective, water repellent bag to store cord and accessories out of the way
- Can be installed to an existing anchor point via ANSI Z359.12 carabiner (not included)
- Can be bolted to I-beams using the Bolt-on Bracket (024-4121) or I-Beam Mount (024-4124) sold separately
- 15-degree angle of use
- Corrosion resistant materials
- Working Load Limit: 1,000 lbs. (453.6 kg)

ATTACHMENT POINT(S):

- 1 D-ring

MINIMUM BREAKING STRENGTH:

- 5,000 lbs. (22 kN)

ITEM WEIGHT:

- 2.8 lbs. (1.3 kg)



USER WEIGHT CAPACITY

ANSI	130-310 lbs. (59-141 kg)
OSHA	Up to 420 lbs. (191 kg)

STANDARD COMPLIANT WITH

ANSI	Z359.18-2017 Type A
OSHA	1926.502, 1910.140, 1910.66

RELATED PRODUCT(S)

024-4121	Shuttle Anchor: Bolt-on Bracket
024-4124	Shuttle Anchor: I-Beam Mount
025-9106	Shuttle Bag

COMPONENT MATERIAL SPECIFICATION

Shuttle Housing	Aluminum
Shuttle Assembly	Stainless steel
D-ring	Steel
Pulley	Nylon
Bag	Polyester
Pull cord	Nylon
Carabiner	Stainless steel with magnet