



## 024-4124

### Shuttle Anchor: I-Beam Mount

#### FEATURES:

- Installs onto horizontal I-beams or vertical I-beams right above a horizontal connection.
- For I-beams with a height between 4-10", and max. width of 11.5"
- Includes bracket, (4) rods, (8) washers, and (8) nuts.
- For connection of Shuttle Anchor (023-4105).
- Not for fall protection use without anchor (sold separately).

#### ATTACHMENT POINT(S):

- N/A

#### MINIMUM BREAKING STRENGTH:

- 5,000 lbs. (22 kN)

#### ITEM WEIGHT:

- 27.6 lbs. (12.5 kg)



#### USER WEIGHT CAPACITY

ANSI	130-310 lbs. (59-141 kg)
OSHA	Up to 420 lbs. (191 kg)

#### STANDARD COMPLIANT WITH

ANSI	N/A
OSHA	N/A

#### RELATED PRODUCT(S)

023-4105	Shuttle Anchor
024-4121	Shuttle Anchor: Bolt-on Bracket
025-9106	Shuttle Anchor Bag

#### COMPONENT MATERIAL SPECIFICATION

Fasteners	YCM-Plated Steel
Bases	YCM-Plated Steel
Bracket	Zinc-plated and EP-coated steel