



Latitude Edge Arc Flash SRL-P

*See chart for part numbers, hook configurations, and product weights

FEATURES :

- Lightweight, durable housing design
- Exclusive dorsal attachment bracket with SRL separator feature.
- Compact Arc Flash shock pack design with harness restraint strap.
- 360/180° attachment point offers full range of motion.
- Side payout for smooth retraction.
- Exclusive edge resistant Kevlar® webbing.
- Protective label cover for product longevity and traceability.
- Single leg and dual leg options available.
- Available with various hook options, see chart.
- All components are Z359.12 compliant.



Class

2

Anchor above or
below dorsal D-ring

Product shown:
025-5506

USER WEIGHT CAPACITY

ANSI	130-310 lbs. (59-141 kg)
OSHA	Up to 420 lbs. (191 kg)

STANDARD COMPLIANT WITH

ANSI	Z359.14-2021
OSHA	1910.140, 1910.66
ASTM	F887

ANSI CLASS 1

Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.3 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 32 in. (81 cm)
Max. free fall distance	24 in. (61 cm)
Min. required fall clearance	6 ft. 2 in. (1.9 m)
For full clearance requirements, see user instructions	

ANSI CLASS 2

Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.3 kg)
Max. arrest distance	N/A
Actual arrest distance	≤ 101 in. (257 cm)
Max. free fall distance	72 in. (183 cm)
Min. required fall clearance	16 ft. 11 in. (5.1 m)
For full clearance requirements, see user instructions	

MATERIAL SPECIFICATION

Web	Kevlar®
Bracket	Stainless steel, steel and aluminum
Housing	Nylon
Hook options	Steel, aluminum, dielectric (dependent on configuration)
Shock pack	Nomex®



SAFEWAZE

TECHNICAL DATA SHEET

Latitude Edge Arc Flash SRL-P

LATITUDE

EDGE ARC FLASH

Standards: ANSI Z359.14-2021

OSHA 1910.140 & 1910.66

ASTM F887

Capacity: ANSI 130-310 lbs. (59-141 kg)

OSHA Up to 420 lbs. (191kg)

CONNECTOR

ATTACHMENT

Part Number	Single Leg (S) / Dual Leg (D)	Working Length (ft.)	Lifeline Material	Lifeline Dimensions (in.)	Housing Material	Weight (lbs.)	U Steel Swivel Snap Hook ①	Steel Snap Hook ②	Dielectric Snap Hook ③	Steel Tie Back Hook ④	U Steel Swivel Rebar Hook ⑤	Steel Swivel Rebar Hook ⑥	Steel Swivel Rebar Hook ⑦	Steel Captive Eye Carabiner ⑧	ALU Captive Eye Carabiner ⑨	ALU Swivel Carabiner ⑩	Trip Lock Steel Carabiner ⑪	Steel Carabiner ⑫	ALU Captive Eye Carabiner ⑬	ALU Captive Eye Carabiner ⑭	ALU Snap Hook ⑮	FS-EX313 ⑯	Cab Mount Bracket ⑰	Soft Loop ⑱	Integrated BWB ⑲	1014 BWB ⑲	9012 BWB ⑲	9013 BWB ⑲
025-5506	2	S	6	Kevlar® 1 x .20	Nylon	4	X																			X		
025-5507	2	S	6	Kevlar® 1 x .20	Nylon	3.6			X																	X		
025-5508	2	S	6	Kevlar® 1 x .20	Nylon	4.8						X														X		
025-5509	2	S	6	Kevlar® 1 x .20	Nylon	4.6								X												X		
025-5510	2	S	6	Kevlar® 1 x .20	Nylon	4				X																X		
025-5551	2	D	6	Kevlar® 1 x .20	Nylon	7.1	X																			X		
025-5552	2	D	6	Kevlar® 1 x .20	Nylon	6.3			X																	X		
025-5553	2	D	6	Kevlar® 1 x .20	Nylon	8.7						X														X		
025-5554	2	D	6	Kevlar® 1 x .20	Nylon	8.3								X												X		
025-5555	2	D	6	Kevlar® 1 x .20	Nylon	7.1				X																X		
025-5511	2	S	8	Kevlar® 1 x .20	Nylon	4.1	X																			X		
025-5512	2	S	8	Kevlar® 1 x .20	Nylon	3.7			X																	X		
025-5513	2	S	8	Kevlar® 1 x .20	Nylon	4.9						X														X		
025-5514	2	S	8	Kevlar® 1 x .20	Nylon	4.7								X												X		
025-5515	2	S	8	Kevlar® 1 x .20	Nylon	4.1				X																X		
025-5556	2	D	8	Kevlar® 1 x .20	Nylon	7.3	X																			X		
025-5557	2	D	8	Kevlar® 1 x .20	Nylon	6.5			X																	X		
025-5558	2	D	8	Kevlar® 1 x .20	Nylon	8.9						X														X		
025-5559	2	D	8	Kevlar® 1 x .20	Nylon	8.5								X												X		
025-5560	2	D	8	Kevlar® 1 x .20	Nylon	7.3				X																X		
025-5516	2	S	10	Kevlar® 1 x .20	Nylon	4.2	X																			X		
025-5517	2	S	10	Kevlar® 1 x .20	Nylon	3.8			X																	X		
025-5518	2	S	10	Kevlar® 1 x .20	Nylon	5						X														X		
025-5519	2	S	10	Kevlar® 1 x .20	Nylon	4.8								X												X		
025-5520	2	S	10	Kevlar® 1 x .20	Nylon	4.2				X																X		
025-5561	2	D	10	Kevlar® 1 x .20	Nylon	7.5	X																			X		
025-5562	2	D	10	Kevlar® 1 x .20	Nylon	6.7			X																	X		
025-5563	2	D	10	Kevlar® 1 x .20	Nylon	9						X														X		
025-5564	2	D	10	Kevlar® 1 x .20	Nylon	8.7								X												X		
025-5565	2	D	10	Kevlar® 1 x .20	Nylon	7.5				X																X		

