



Latitude Edge Cable SRL-P

*See chart for part numbers, hook configurations, and product weights

FEATURES :

- Durable stainless steel housing with nylon sides
- Frameless design creates thinner housing size
- Exclusive dorsal attachment bracket with SRL separator feature
- Compact shock pack design with harness restraint strap
- 360/180° attachment point offers full range of motion.
- Side payout for smooth retraction
- Protective label cover for product longevity and traceability
- RFID equipped
- Designed for sharp leading edges with foot-level connection
- 6' and 8' lengths available
- Single leg and dual leg options available
- Available with various hook options, see chart
- All components are Z359.12 compliant



Class

2

Anchor above or
below dorsal D-ring

Product shown:
023-5350

USER WEIGHT CAPACITY

ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

STANDARD COMPLIANT WITH

ANSI	Z359.14-2021
OSHA	1910.140, 1910.66

ANSI CLASS 1

Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.3 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 36 in. (91 cm)
Max. free fall distance	24 in. (61 cm)
Min. required fall clearance	6 ft. 6 in. (2 m)
For full clearance requirements, see user instructions	

ANSI CLASS 2

Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.3 kg)
Max. arrest distance	N/A
Actual arrest distance	≤ 83 in. (211 cm)
Max. free fall distance	72 in. (183 cm)
Min. required fall clearance	15 ft. 5 in. (4.7 m)
For full clearance requirements, see user instructions	

MATERIAL SPECIFICATION

Cable	3/16" galvanized steel
Bracket	Steel and aluminum
Housing	Stainless steel and nylon
Hook options	Steel, aluminum, dielectric (dependent on configuration)
Shock pack	Polyester



SAFEWAZE

TECHNICAL DATA SHEET

Latitude Edge Cable SRL-P



Standards: ANSI Z359.14-2021
OSHA 1910.140 & 1910.66

Capacity: ANSI 130-310 lbs. (59-141 kg)
OSHA Up to 420 lbs. (191kg)

CONNECTOR

ATTACHMENT

Part Number	Single Leg (S) / Dual Leg (D)	Working Length (ft.)	Lifeline Material	Lifeline Dimensions (in.)	Housing Material	Weight (lbs.)	LI Steel Swivel Snap Hook	Steel Snap Hook	Dielectric Snap Hook	Steel Tie Back Hook	LI Steel Swivel Rebar Hook	Steel Swivel Rebar Hook	Steel Swivel Rebar Hook	ALU Swivel Rebar Hook	Steel Captive Eye Carabiner	ALU Captive Eye Carabiner	ALU Swivel Carabiner	Tripp Lock Steel Carabiner	Steel Carabiner	ALU Captive Eye Carabiner	ALU Swivel Carabiner	FS-EX313	Gab Mount Bracket	Integrated BWB	1014 BWB	9012 BWB	9013 BWB
025-5609	2	S	6	Steel Cable	Ø3/16	Nylon/SS	4.4	X																	X		
025-5610	2	S	6	Steel Cable	Ø3/16	Nylon/SS	5.2					X													X		
025-5611	2	S	6	Steel Cable	Ø3/16	Nylon/SS	4.0			X															X		
025-5612	2	S	6	Steel Cable	Ø3/16	Nylon/SS	5.0								X										X		
025-5613	2	S	6	Steel Cable	Ø3/16	Nylon/SS	3.8										X								X		
025-5614	2	D	6	Steel Cable	Ø3/16	Nylon/SS	7.6	X																	X		
025-5615	2	D	6	Steel Cable	Ø3/16	Nylon/SS	9.2					X													X		
025-5616	2	D	6	Steel Cable	Ø3/16	Nylon/SS	6.8			X															X		
025-5607	2	D	6	Steel Cable	Ø3/16	Nylon/SS	8.8								X										X		
025-5617	2	D	6	Steel Cable	Ø3/16	Nylon/SS	6.4										X								X		
023-5350	2	S	8	Steel Cable	Ø3/16	Nylon/SS	4.6	X																	X		
023-5351	2	S	8	Steel Cable	Ø3/16	Nylon/SS	5.4					X													X		
023-5352	2	S	8	Steel Cable	Ø3/16	Nylon/SS	4.2			X															X		
023-5353	2	S	8	Steel Cable	Ø3/16	Nylon/SS	5.2										X								X		
023-5354	2	S	8	Steel Cable	Ø3/16	Nylon/SS	4.0											X							X		
023-5355	2	D	8	Steel Cable	Ø3/16	Nylon/SS	7.8	X																	X		
023-5356	2	D	8	Steel Cable	Ø3/16	Nylon/SS	9.4					X													X		
023-5357	2	D	8	Steel Cable	Ø3/16	Nylon/SS	7.0			X															X		
023-5358	2	D	8	Steel Cable	Ø3/16	Nylon/SS	9.0										X								X		
023-5359	2	D	8	Steel Cable	Ø3/16	Nylon/SS	6.6										X								X		

