



Lodestar Lift Arc Flash Web SRL

*See chart for part numbers, hook configurations, and product weights

FEATURES :

- Lightweight, durable housing design providing protection against Arc Flash hazards
- Compact Arc Flash resistant shockpack
- Exclusive edge resistant Kevlar® webbing
- Designed for sharp leading edges with foot-level connection
- 360/180° attachment point swivels for full range of motion
- Single leg leg options available
- Warning tag on top of housing to denote anchor connection
- Available with various hook options, see chart
- All components are Z359.12 compliant
- ***Not an SRL-P***

Class
2
Anchor above or
below dorsal D-ring



Product shown:
025-5527

USER WEIGHT CAPACITY

ANSI	130-310 lbs. (59-141 kg)
OSHA	Up to 420 lbs. (191 kg)

STANDARD COMPLIANT WITH

ANSI	Z359.14-2021
OSHA	1910.140, 1910.66
ASTM	F887

ANSI CLASS 1

Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.3 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 26 in. (66 cm)
Max. free fall distance	24 in. (61 cm)
Min. required fall clearance	5 ft. 8 in. (1.7 m)
For full clearance requirements, see user instructions	

ANSI CLASS 2

Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.3 kg)
Max. arrest distance	N/A
Actual arrest distance	≤ 105 in (267 cm)
Max. free fall distance	72 in. (183 cm)
Min. required fall clearance	17 ft. 3 in. (5.3 m)
For full clearance requirements, see user instructions	

MATERIAL SPECIFICATION

Web	Kevlar®
Carabiner	YCM plated steel
Housing	Nylon
Hook options	Steel, aluminum, dielectric (dependent on configuration)
Shock pack	Polyester, Nomex®



Lodestar Lift Arc Flash Web SRL



Standards: ANSI Z359.14-2021

OSHA 1910.140 & 1910.66

ASTM F887

Capacity: ANSI 130-310 lbs. (59-141 kg)

OSHA Up to 420 lbs. (191kg)

CONNECTOR													ATTACHMENT																								
Part Number	Single Leg (S) / Dual Leg (D)		Working Length (ft.)		Lifeline Material		Lifeline Dimensions (in.)		Housing Material		Weight (lbs.)		LI Steel Swivel Snap Hook ①	LI Steel Swivel Snap Hook ②	Dielectric Snap Hook ③	Steel Tie Back Hook ④	LI Steel Swivel Rebar Hook ⑤	Steel Swivel Rebar Hook ⑥	Steel Swivel Rebar Hook ⑦	Steel Captive Eye Carabiner ⑧	ALU Rebar Hook ⑨	ALU Captive Eye Carabiner ⑩	ALU Swivel Carabiner ⑪	No Attachment ⑫	Tripp Lock Steel Carabiner ⑬	ALU Captive Eye Carabiner ⑭	ALU Carabiner ⑮	ALU Snap Hook ⑰	FS-EX313 ⑱	Gal Mount Bracket ⑲	Integrated BWB ⑳	Soft Loop ㉑	1014 BWB ㉒	9012 BWB ㉓	9013 BWB ㉔		
025-5527	2	S	6	Kevlar*	1 x .20	Nylon	3.9		X																	X											
025-5528	2	S	6	Kevlar*	1 x .20	Nylon	3.5								X											X											
025-5529	2	S	6	Kevlar*	1 x .20	Nylon	3.5																X			X											
025-5530	2	S	6	Kevlar*	1 x .20	Nylon	4									X										X											
025-5531	2	S	8	Kevlar*	1 x .20	Nylon	4	X																		X											
025-5532	2	S	8	Kevlar*	1 x .20	Nylon	3.6								X											X											
025-5533	2	S	8	Kevlar*	1 x .20	Nylon	3.6																X			X											
025-5534	2	S	8	Kevlar*	1 x .20	Nylon	4.1									X										X											
025-5535	2	S	10	Kevlar*	1 x .20	Nylon	4.1	X																		X											
025-5536	2	S	10	Kevlar*	1 x .20	Nylon	3.7								X											X											
025-5537	2	S	10	Kevlar*	1 x .20	Nylon	3.7																X			X											
025-5538	2	S	10	Kevlar*	1 x .20	Nylon	4.2									X										X											

