



Lodestar Lift Web SRL

*See chart for part numbers, hook configurations, and product weights

FEATURES :

- Lightweight, durable housing design
- Compact shockpack
- Exclusive edge resistant composite webbing
- 360/180° attachment point swivels for full range of motion
- Designed for sharp leading edges with foot-level connection
- Single leg leg options available
- Warning tag on top of housing to denote anchor connection
- Available with various hook options, see chart
- All components are Z359.12 compliant
- ***Not an SRL-P***



Class

2

Anchor above or below dorsal D-ring

Product shown:
024-5410

USER WEIGHT CAPACITY

ANSI	130-310 lbs. (59-141 kg)
OSHA	Up to 420 lbs. (191 kg)

STANDARD COMPLIANT WITH

ANSI	Z359.14-2021
OSHA	1910.140, 1910.66

ANSI CLASS 1

Max. arrest force	≤ 1,800 lbs. (817 kg)
Avg. arrest force	≤ 1,350 lbs. (612 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 26 in. (66 cm)
Max. free fall distance	24 in. (61 cm)
Min. required fall clearance	5 ft. 8 in. (1.7 m)
For full clearance requirements, see user instructions	

ANSI CLASS 2

Max. arrest force	≤ 1,800 lbs. (817 kg)
Avg. arrest force	≤ 1,350 lbs. (612 kg)
Max. arrest distance	N/A
Actual arrest distance	≤ 105 in (267 cm)
Max. free fall distance	72 in. (183 cm)
Min. required fall clearance	17 ft. 3 in. (5.3 m)
For full clearance requirements, see user instructions	

MATERIAL SPECIFICATION

Web	Specialized Composite
Carabiner	YCM plated steel
Housing	Nylon
Hook options	Steel and aluminum (dependent on configuration)
Shock pack	Polyester and tarpaulin



Lodestar Lift Web SRL



Standards: ANSI Z359.14-2021
OSHA 1910.140 & 1910.66

Capacity: ANSI 130-310 lbs. (59-141 kg)
OSHA Up to 420 lbs. (191kg)

CONNECTOR

ATTACHMENT

Part Number	Single Leg (S) / Dual Leg (D)	Working Length (ft.)	Lifeline Material	Housing Dimensions (in.)	Housing Material	Weight (lbs.)	LI Steel Swivel Snap Hook ①	LI Steel Swivel Snap Hook ②	Dielectric Snap Hook ③	Steel Tie Back Hook ④	Steel Rebar Hook ⑤	Steel Swivel Rebar Hook ⑥	Steel Swivel Rebar Hook ⑦	Steel Captive Eye Carabiner ⑧	ALU Captive Eye Carabiner ⑨	ALU Swivel Carabiner ⑩	Tripp Lock Steel Carabiner ⑪	Steel Carabiner ⑫	ALU Captive Eye Carabiner ⑬	ALU Captive Eye Carabiner ⑭	ALU Swivel Hook ⑮	FS-EX313 ⑯	Cab Mount Bracket ⑰	Soft Loop ⑱	Integrated BWB ⑲	1014 BWB ⑳	9012 BWB ㉑	9013 BWB ㉒
024-5410	2	S	6	Composite	1 x.15	Nylon	4	X										X										
024-5411	2	S	6	Composite	1 x.15	Nylon	3.6			X								X										
024-5412	2	S	6	Composite	1 x.15	Nylon	3.6									X		X										
025-5521	2	S	8	Composite	1 x.15	Nylon	4.1	X										X										
025-5522	2	S	8	Composite	1 x.15	Nylon	3.7			X								X										
025-5523	2	S	8	Composite	1 x.15	Nylon	3.7									X		X										
025-5524	2	S	11	Composite	1 x.15	Nylon	4.2	X										X										
025-5525	2	S	11	Composite	1 x.15	Nylon	3.8			X								X										
025-5526	2	S	11	Composite	1 x.15	Nylon	3.8									X		X										

