



025-1837 through 025-1840

V-Select Hot Work CH: 3D, QC Chest, TB Legs

FEATURES :

- Fixed dorsal D-ring
- Integrated SRL channel
- Side positioning D-rings
- Quick-connect chest
- Friction buckle torso adjusters
- Tongue buckle legs
- Breakaway lanyard keepers
- Label cover with size indicator
- Shoulder pad
- Fixed waist pad
- 40 Cal rated aramid webbing
- Char rating 600°

FALL ARREST POINT(S) :

- 1 Dorsal D-ring

ITEM WEIGHT :

- 7 lbs. (3.2 kg)



DORSAL ATTACHMENT



WAIST ATTACHMENT

USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-141 kg)
OSHA	Up to 420 lbs. (191 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.11-2021
OSHA	1926.502, 1910.140

SIZE(S)	
025-1837	X-Small / Small
025-1838	Medium / Large
025-1839	X-Large / 2X
025-1840	3X

COMPONENT	MATERIAL SPECIFICATION
Webbing	Aramid/ Polyester
D-ring(s)	Zinc-plated steel with EP coating
Adjuster buckles	Zinc-plated steel with EP coating
Chest connection	Zinc-plated steel with EP coating
Leg connection	Zinc-plated steel with EP coated buckle, stainless steel gromets
Pads	EVA foam, fiberglass and polyester
Label cover	Fiberglass and polyester
Belt	Aramid/PE webbing, zinc-plated steel w/ EP coated buckle, stainless steel Grommets