



## 025-1953 through 025-1956

### V-Select Construction Harness: 3D, QC Chest, FD, TB Legs, Trauma Relief

#### FEATURES:

- Fixed dorsal D-ring
- Integrated SRL channel
- Front D-ring
- Side positioning D-rings
- Friction buckle torso adjusters
- Quick-connect chest
- Tongue buckle legs
- Breakaway lanyard keepers
- Label cover with size indicator
- Fixed shoulder pad
- Fixed waist pad
- Integrated trauma packs

#### FALL ARREST POINT(S):

- 1 Dorsal D-ring
- 1 Dorsal SRL channel

#### ITEM WEIGHT:

- 6.6 lbs. ( 3 kg)



USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-141 kg)
OSHA	Up to 420 lbs. (191 kg)

SIZE(S)	
025-1953	X-Small / Small
025-1954	Medium / Large
025-1955	X-Large / 2X
025-1956	3X

STANDARD COMPLIANT WITH	
ANSI	Z359.11-2021
OSHA	1926.502, 1910.140

COMPONENT	MATERIAL SPECIFICATION
Webbing	Polyester
D-ring(s)	Stamped zinc-plated steel with EP coating
Adjuster buckles	Zinc-plated steel with EP coating
Chest connection	Zinc-plated steel with EP coating
Leg connection	Zinc-plated steel with EP coated buckle, stainless steel grommets
Pads	EVA and NBR foam, polyester
Lanyard keepers	Nylon
Belt	Polyester webbing, zinc-plated steel with EP coated buckle, stainless steel grommets
Trauma packs	Polyester