



019-2015

Leading Edge 6' Energy Absorbing Lanyard: Dual Leg, Alu Swivel Snap Hooks

FEATURES :

- 6' free fall when used overhead
- 12' free fall in leading edge and some other scenarios depending on anchorage point
- 1/4" hi-vis coated green cable
- 1 forged aluminium snap hook
- 2 forged aluminum swivel snap hooks
- Dual leg construction
- Ballistic shock pack with label cover
- Minimum Breaking Strength: 5,000 lbs.
- All components are ANSI Z359.12 Compliant

ATTACHMENT POINT(S) :

- 1 Snap Hook
- 2 Swivel Snap Hooks

ITEM LENGTH :

- 6' (1.8 m)

ITEM WEIGHT :

- 4.6 lbs. (2.1 kg)

**USER WEIGHT CAPACITY**

ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (191 kg)

STANDARD COMPLIANT WITH

ANSI	Z359.13-2013
OSHA	1926.502, 1910.140, 1910.66

SIZE(S)

N/A	

COMPONENT**MATERIAL SPECIFICATION**

Cable	1/4" coated steel
Snap Hook	Forged aluminium
Shock Cover	Polyester
Swivel Snap Hook	Forged aluminium