



019-4006

FrogLink Permanent/Temp Roof Anchor with Rivets

FEATURES :

- Can be used as a single point anchor or as part of a horizontal lifeline system
- 360° working radius
- Built-in energy absorber reduces stress or damage to the mounting structure
- Installs on metal roofs min. 26 gauge using (7) 8 mm Bulb Rivets (included)
- Can also be installed in concrete slab 3,000 PSI or greater with min. 3" thickness using (4) 1/4" x 1-3/4" hex head tapcon concrete screws (not included)
- Max. anchor deformation in a fall event is 9"
- Minimum Breaking Strength (MBS): 3,600 lbs. (16 kN)
- Dimensions: 8.25" x 4.25" x 1.5" (21 cm x 10.8 cm x 3.8 cm)

FALL ARREST POINT(S) :

- 1 Formed Loop

ITEM WEIGHT :

- 0.8 lbs. (0.4 kg)

**USER WEIGHT CAPACITY**

ANSI	130-310 lbs. (59-141 kg)
OSHA	N/A

STANDARD COMPLIANT WITH

ANSI	N/A
OSHA	1926.502, 1910.140, 1910.66

SIZE(S)

N/A	

COMPONENT**MATERIAL SPECIFICATION**

Anchor	Stainless Steel
Rivets	Aluminum Body, Mandrel; Neoprene Washer