



020-1250 through 020-1256

Arc Flash Construction Harness : DE 3D, DE QC Chest, DE FD, DE QC Legs

FEATURES :

- Fixed dorsal D-ring
- Integrated SRL channel
- Front D-ring
- Side D-rings
- Quick-connect chest
- Mating buckle torso adjusters
- Quick-connect legs
- Shoulder pad
- Fixed waist pad with quick-connect belt
- Fixed leg pads
- 40 Cal rated aramid webbing

FALL ARREST POINT(S) :

- 1 Dorsal D-ring

ITEM WEIGHT :

- 5.7 lbs. (2.6 kg)



| USER WEIGHT CAPACITY | |
|----------------------|--------------------------|
| ANSI | 130-310 lbs. (59-141 kg) |
| OSHA | Up to 420 lbs. (191 kg) |

| STANDARD COMPLIANT WITH | |
|-------------------------|--------------------|
| ANSI | Z359.11-2021 |
| OSHA | 1926.502, 1910.140 |
| ASTM | F887 |

| SIZE(S) | |
|----------|---------|
| 020-1250 | X-Small |
| 020-1251 | Small |
| 020-1252 | Medium |
| 020-1253 | Large |
| 020-1254 | X-Large |
| 020-1255 | 2X |
| 020-1256 | 3X |
| | |

| COMPONENT | MATERIAL SPECIFICATION |
|------------------|---------------------------------|
| Webbing | Aramid |
| D-ring(s) | Dielectric coated steel |
| Adjuster buckles | Dielectric coated steel |
| Chest connection | Dielectric coated steel |
| Leg connection | Dielectric coated steel |
| Pads | Nomex ® |
| Belt | Aramid; Dielectric coated steel |
| SRL Channel | TPU polycarbonate |