



024-4115

Standing Seam Bar Anchor: Steel Screws

FEATURES :

- Easy to install, reusable non-penetrating anchor point
- 360° swivel D-ring connection point for SRLs, energy absorbing lanyards and VLLs
- Accommodates a wide range of standing seams
- For sloped or flat standing seam roofs with minimum gauge 26
- (12) Stainless steel set screws
- 1 user maximum
- Minimum Breaking Strength: 5,000 lbs. (22 kN)
- Dimensions: 8" x 2.25" x 4.5" (20x5.7x11.5 cm)
- Can be used for HLL use ONLY if installed on steel plates, beams, or angle iron
- Not suitable for material hauling use

ATTACHMENT POINT(S) :

- 1 Swivel D-ring

ITEM WEIGHT :

- 3 lbs. (1.4 kg)



USER WEIGHT CAPACITY

ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (191 kg)

STANDARD COMPLIANT WITH

ANSI	N/A
OSHA	1926.502, 1910.140, 1910.66

COMPATIBLE COMPONENTS

025-4126	Standing Seam Bar Anchor: Nylon Tipped Screws
025-4127	Standing Seam Nylon-Tipped Set Screws (Set of 12)
025-4128	Standing Seam Steel Set Screws (Set of 12)

COMPONENT

MATERIAL SPECIFICATION

Anchor	Aluminum
D-ring	Stainless Steel
Set Screws	Stainless Steel
Label Cover	Polyester