



024-5396

Northstar Classic 30' Web SRL

*See chart for additional part numbers, hook configurations, and product weights

FEATURES :

- High strength polymer housing resists impact
- Braking system activates quickly to arrest fall
- Load indicating swivel snap hook easily identifies when product has arrested a fall
- All components are Z359.12 compliant



Class
1
Anchor at or above dorsal D-ring

USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-141 kg)
OSHA	Up to 420 lbs. (191 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.14-2021
OSHA	1910.140, 1910.66, 1926.502

ANSI CLASS 1 (ABOVE D-RING)	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 900 lbs. (408.2 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 29 in. (4 cm)
Max. free fall distance	24 in. (61 cm)
Min. required fall clearance	5 ft. 11 in. (1.8 m)
For full clearance requirements, see user instructions	

MATERIAL SPECIFICATION	
Housing	Nylon and glass fiber
Snap Hook	YCM plated steel
Carabiner	YCM plated steel
Webbing	1" UHMWPE

