



025-11055

65' Technical Personnel Winch- Cable

FEATURES :

- Designed for personnel riding applications
 - Powered capabilities using the torque limiting coupler (025-11059) and standard drill
 - Counter to track maintenance
 - Knob to transition into Freewheel mode
 - Corrosion resistant cable
 - Removable handle with storage slot
 - Comes with Device Bracket installed, tripod mounting bracket not included
 - Max. operation force: ≤ 30 lbs. (13.6 kg)
 - 1:4 manual gear ratio
 - 1:18.9 power gear ratio
 - Material lifting capacity: 620 lbs. (281 kg)
 - Max. working length: 65' (19.8 m)
 - Max service interval: 10,000 cycles
- ***eligible for service and repair***

FALL ARREST POINT(S) :

- 1 Swivel snap hook

ITEM WEIGHT :

- 35 lbs. (16 kg)



| USER WEIGHT CAPACITY | |
|----------------------|--------------------------|
| ANSI | 130-310 lbs. (59-141 kg) |
| OSHA | Up to 420 lbs. (191 kg) |

| STANDARD COMPLIANT WITH | |
|-------------------------|-----------------------------|
| ANSI | Z359.4-2013, Z117.1-2022 |
| OSHA | 1926.502, 1910.140, 1910.66 |

| COMPATIBLE COMPONENTS | |
|-----------------------|---------------------------------|
| 025-11059 | Torque Limiting Coupler |
| 025-11060 | Replacement Handle |
| 022-11029 | 10' Tech Tripod Basic |
| 020-11025 | Aluminum Tripod Pulley |
| FS970-PK | Tripod Pulley |
| 019-11010 | Universal Tripod Bracket |
| 024-11047 | Competitor Uni mounting bracket |
| 019-11000 | 7' Adjustable Tripod |

| COMPONENT | MATERIAL SPECIFICATION |
|----------------|--------------------------|
| Housing | Aluminum |
| Handles | Aluminum w/ rubber grips |
| Cable | 7/32" Galvanized steel |
| Snap hook | YCM-plated steel |
| Device Bracket | Zinc-plated steel |
| Detent Pins | Stainless Steel |
| | |
| | |