

**Removable Concrete Anchor Use**

Subject: Clarification of Removable Concrete Anchor Use Allowances
Related Products: 022-4085
Related Standards: ANSI Z359.18-2017 Type T & OSHA 1926.502, 1910.140, 1910.66
Date: 04-13-2026
Revision: 2

The Safewaze 022-4085 Removable Concrete Anchor is a versatile ANSI Z359.18-2017 Type T anchor with a Minimum Breaking Strength of 10,000 lbs. (44 kN) and a Working Load Limit of 1,800 lbs. (8 kN) in 4,000 PSI, or higher, concrete. The Removable Concrete Anchor is suitable for use as a fall arrest anchor point. Additionally, the 022-4085 can be used for safety lines, tie-back lines (except on swing stages), and material hauling applications.

However, the anchor cannot be used as a fall arrest anchor point after it is used for any purposes outside of personal fall protection. For example, if the Removable Concrete Anchor is used for material hauling, the anchor must then be clearly labeled and used for material work/working load use only.

Whether the anchor is used for fall protection, safety lines, tie-back lines, or material hauling, a Competent Person must determine the overall system is capable of withstanding anticipated fall loads and meets, or exceeds, OSHA required anchorage strength regulations. The manufacturer's instructions should always be read, understood, and followed for all components and subsystems in the Personal Fall Arrest System (PFAS).

For questions regarding the information in this Technical Bulletin, please contact Customer Service at (800) 230-0319.

022-4085: