



FS66150

PRO 6' Stretch Internal Energy Absorbing Lanyard: Dual Leg, O-Ring, Rebar Hooks

FEATURES :

- Stretches from 4' to 6'
- 1-3/8" elasticized Poly/POY web
- 1 forged steel snap hook
- 2 forged steel rebar hooks
- 1 SRL O-ring connection
- Dual leg construction
- Ballistic shock pack with label cover
- Minimum Breaking Strength: 5,000 lbs.
- All components are ANSI Z359.12 Compliant

ATTACHMENT POINT(S) :

- 1 Snap Hook
- 2 Rebar Hooks
- 1 SRL O-ring Connection

ITEM LENGTH :

- 4'-6' (1.2-1.8 m)

ITEM WEIGHT :

- 6.4 lbs. (2.9 kg)



USER WEIGHT CAPACITY

ANSI	130-310 lbs. (59-140.6 kg)
OSHA	N/A

STANDARD COMPLIANT WITH

ANSI	Z359.13-2013
OSHA	1926.502, 1910.140, 1910.66

SIZE(S)

N/A	

COMPONENT

MATERIAL SPECIFICATION

Webbing	1-3/8" Elasticated Poly/POY
Snap Hook	Forged zinc plated steel
Shock Cover	Polyester
Rebar Hook	Forged zinc plated steel
O-ring	Forged steel