



## FS77430-WE-DL

### Welding 6' Energy Absorbing Lanyard: Dual Leg, Snap Hook

#### FEATURES :

- 40Cal/700F rated
- 1-3/4" dual layer Aramid webbing
- 3 forged steel snap hook
- Dual leg construction
- Nomex® shock pack and label cover
- Minimum Breaking Strength: 5,000 lbs.
- All components are ANSI Z359.12 Compliant

#### ATTACHMENT POINT(S) :

- 3 Snap Hooks

#### ITEM LENGTH :

- 6' (1.8 m)

#### ITEM WEIGHT :

- 4 lbs. (1.8 kg)



#### USER WEIGHT CAPACITY

|      |                            |
|------|----------------------------|
| ANSI | 130-310 lbs. (59-140.6 kg) |
| OSHA | N/A                        |

#### STANDARD COMPLIANT WITH

|      |                             |
|------|-----------------------------|
| ANSI | Z359.13-2013                |
| OSHA | 1926.502, 1910.140, 1910.66 |

#### SIZE(S)

|     |  |
|-----|--|
| N/A |  |
|     |  |
|     |  |
|     |  |
|     |  |
|     |  |
|     |  |
|     |  |

#### COMPONENT

#### MATERIAL SPECIFICATION

|             |                          |
|-------------|--------------------------|
| Webbing     | 1-3/4" dual layer Aramid |
| Wear sleeve | Aramid                   |
| Snap Hook   | Forged zinc plated steel |
| Shock Cover | Nomex®                   |
|             |                          |
|             |                          |
|             |                          |
|             |                          |