



## FS810

### Reinforced Cross Arm Strap

**FEATURES:**

- Mobile anchor point solution
- Lightweight and portable
- Reusable
- Easy to install
- Durable heavyweight webbing
- Abrasion resistant sling webbing wear pad
- Multiple lengths

**MINIMUM BREAKING STRENGTH:**

- 5,000 lbs. (22 kN)

**FALL ARREST POINT(S):**

- 2 D-rings

**ITEM WEIGHT:**

- Varies by length (see chart below)



USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-141 kg)
OSHA	Up to 420 lbs. (191 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.18-2017 Type T
OSHA	1926.502, 1910.140, 1910.66

SIZES/WEIGHTS	
FS810-3 (3')	0.8 lbs. (0.4 kg)
FS810-4 (4')	0.9 lbs. (0.4 kg)
FS810-6 (6')	1.2 lbs. (0.5 kg)
FS810-8 (8')	1.5 lbs. (0.7 kg)
FS810-10 (10')	1.8 lbs. (0.8 kg)
FS810-12 (12')	2.1 lbs. (1 kg)
FS810-15 (15')	2.5 lbs. (1.1 kg)
FS810-20 (20')	3.2 lbs. (1.5 kg)

COMPONENT	MATERIAL SPECIFICATION
Webbing	Polyester
D-rings	Zinc-plated steel