



Latitude 37" Tie-Back 6' Web SRL-P

*See chart for part numbers, hook configurations, and product weights

FEATURES :

- Quick-locking unit designed for use at low heights.
- 360/180° attachment point offers full range of motion.
- Durable housing increases strength and longevity.
- External shock pack with energy absorber and protective label cover.
- High-strength, lightweight webbing.
- 37" replaceable tie-back legs, single leg and dual leg options available.
- Available with various hook options, see chart.
- All components are Z359.12 compliant.



Product shown:
021-5278

USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-141 kg)
OSHA	Up to 420 lbs. (191 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.14-2021
OSHA	1910.140, 1910.66

ANSI CLASS 1 (ABOVE D-RING)	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.4 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 23 in (58 cm)
Max. free fall distance	24 in. (61 cm)
Use below d-ring	not permitted
Min. required fall clearance	5 ft. 5 in. (1.7 m)
For full clearance requirements, see user instructions	

ANSI CLASS 1 (ABOVE D-RING)	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.4 kg)
Max. arrest distance	
Actual arrest distance	*See product manual
Max. free fall distance	*See product manual
Use below d-ring	*See product manual
Min. required fall clearance	*See product manual
For full clearance requirements, see user instructions	

MATERIAL SPECIFICATION	
Webbing	20 mm UHMPE, polyester
Housing	Nylon
Bracket	Steel, aluminum (dependent on configuration)
Hook options	Steel, aluminum, dielectric (dependent on configuration)
Shock pack	Polyester
O-rings	Zinc plated steel

