

## A SEAMLESS SOLUTION FOR STANDING SEAM ROOFS

Standing seam roofs vary by application, crew movement and attachment method. Safewaze offers multiple non-penetrating anchor solutions so you can match the anchor to how the work is actually performed.

Nylon-tip screws offer non-marring contact to protect roof panels



### 025-4126 / STANDING SEAM BAR ANCHOR: NYLON TIPPED SCREWS

- Easy to install, reusable, non-penetrating anchor point
- 360° swivel D-ring for SRLs, EA lanyards and VLLs
- For use on sloped or flat standing seam roofs
- Accommodates a wider range of standing seam profiles than standard S-5-U clamps

024-4115 / Standing Seam Bar Anchor: Steel Screw

**BEST FOR SINGLE-USER TIE-OFF OR SHORT-DURATION TASKS**



### 025-4129 / STANDING SEAM HLL ANCHOR

- Easy to install, reusable non-penetrating
- Designed for pitched or flat standing seam roofs
- Adjustable crossarm spans 24"-40"
- 360° swivel D-ring for SRL-Ps, EA lanyards, VLLs and HLLs

**BEST FOR MULTIPLE USERS AND LONG ROOF RUNS**



### 023-4096 / STANDING SEAM SWIVEL ANCHOR

- Easy to install, reusable, non-penetrating
- Adjustable crossarm spans 24"-40"
- 360° swivel D-ring for SRL-Ps, EA lanyards and VLLs
- Includes (4) S-5-U brackets

**BEST FOR SIMPLE, FIXED TIE-OFF POINTS**



### 023-4095 / STANDING SEAM SRL SWIVEL ANCHOR

- Easy to install, reusable, non-penetrating
- Adjustable crossarm spans 24"-40"
- 360° swivel base fits most SRL sizes
- Quickly attach SRL directly to post
- D-ring for EA lanyards, VLLs and HLLs
- Includes (6) S-5-U brackets

**BEST FOR CREWS USING SRLS AND FREQUENT MOVEMENT**