



025-1624 through 025-1631

PRO+ Slate FBH: Alu 1D, Alu FD, Alu QC Chest/Legs, Trauma relief

FEATURES :

- Fixed dorsal D-ring
- Integrated SRL channel
- Quick-connect chest
- Front D-ring
- Quick torso adjusters
- Quick-connect legs
- Shoulder pad
- Removable leg pads
- Integrated Quick-Adjust Trauma Relief packs (022-6047) installed on the harness for temporary relief while awaiting rescue.

FALL ARREST POINT(S) :

- 1 Dorsal D-ring
- 1 integrated SRL channel

ITEM WEIGHT :

- 4.9 lbs. (2.2 kg)



USER WEIGHT CAPACITY

ANSI	130-310 lbs. (59-141 kg)
OSHA	Up to 420 lbs. (191 kg)

STANDARD COMPLIANT WITH

ANSI	Z359.11-2021
OSHA	1926.502, 1910.140

SIZE(S)

025-1624	X-Small
025-1625	Small
025-1626	Medium
025-1627	Large
025-1628	X-Large
025-1629	2X
025-1630	3X
025-1631	4X

COMPONENT

MATERIAL SPECIFICATION

Webbing	Polyester
D-ring	Anodized aluminum
Adjuster buckles	Anodized aluminum
Chest connection	Anodized aluminum
Leg connection	Anodized aluminum
SRL channel	HDPE
Pads	Nubuck synthetic; Spandex; Poly mesh; EVA
Trauma Relief	Polyester, EP coated stainless steel, Velcro