



026-1085 through 026-1092

PRO+ Slate Construction Harness : Alu 3D, Alu QC Chest, Alu FD, Alu QC Legs, Trauma Relief

FEATURES :

- Fixed dorsal D-ring
- Integrated SRL channel
- Front D-ring
- Side positioning D-rings
- Quick-connect chest
- Quick torso adjusters
- Quick-connect legs
- Shoulder pad
- Fixed comfort waist pad
- Removable leg pads
- Quick-Adjust Trauma Relief

FALL ARREST POINT(S) :

- 1 Dorsal D-ring
- 1 integrated SRL channel

ITEM WEIGHT :

- 6.6 lbs. (3.0 kg)



USER WEIGHT CAPACITY

ANSI	130-310 lbs. (59-141 kg)
OSHA	Up to 420 lbs. (191 kg)

STANDARD COMPLIANT WITH

ANSI	Z359.11-2021
OSHA	1926.502, 1910.140

SIZE(S)

026-1085	X-Small
026-1086	Small
026-1087	Medium
026-1088	Large
026-1089	X-Large
026-1090	2X
026-1091	3X
026-1092	4X

COMPONENT

MATERIAL SPECIFICATION

Webbing	Polyester
D-ring(s)	Anodized aluminum
Adjuster buckles	Anodized aluminum
Chest connection	Anodized aluminum
Leg connection	Anodized aluminum
SRL channel	HDPE
Pads	Nubuck synthetic; Spandex; Poly mesh; EVA
Belt	Polyester; Steel; Stainless steel
Trauma relief	Polyester, EP coated steel, elastic, velcro