



Latitude Pro 11' Web SRL-P

*See chart for part numbers, hook configurations, and product weights

FEATURES :

- Reliable internal braking system eliminates need for external shock pack.
- High strength semi-sealed assembly protects internal components from debris to extend product life.
- Translucent housing allows easy inspection of webbing, reserve line and pawl assembly.
- 360/180° attachment point offers full range of motion.
- Single leg and dual leg options available.
- Protective label cover for product longevity and traceability.
- Available with various hook options, see chart.
- All components are Z359.12 compliant.

Class

1

Anchor at or above dorsal D-ring



Product shown:
024-5438

USER WEIGHT CAPACITY

ANSI	130-310 lbs. (59-141 kg)
OSHA	Up to 420 lbs. (191 kg)

STANDARD COMPLIANT WITH

ANSI	Z359.14-2021
OSHA	1910.140, 1910.66

ANSI CLASS 1 (ABOVE D-RING)

Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.4 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 39 in. (99 cm)
Max. free fall distance	24 in. (61 cm)
Use below d-ring	not permitted
Min. required fall clearance	6 ft. 9 in. (2.1 m)
For full clearance requirements, see user instructions	

OSHA (BELOW D-RING)

Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 900 lbs. (408.2 kg)
Max. arrest distance	N/A
Actual arrest distance	≤ 53 in. (135 cm)
Max. free fall distance	24 in. (61 cm)
Use below d-ring	2 ft. (0.6 m)
Min. required fall clearance	9 ft. 11 in. (3 m)
For full clearance requirements, see user instructions	

MATERIAL SPECIFICATION

Webbing	20 mm Dyneema® webbing
Housing	Clear resin
Bracket	Steel, aluminum (dependent on configuration)
Hook options	Steel, aluminum, dielectric (dependent on configuration)



SAFEWAZE

TECHNICAL DATA SHEET

Latitude Pro 11' Web SRL-P

LATITUDE

PRO

Standards: ANSI Z359.14-2021
OSHA 1910.140, 1910.66

Capacity: ANSI 130-310 lbs. (59-141 kg)
OSHA Up to 420 lbs. (191kg)

CONNECTOR

ATTACHMENT

Part Number	Single Leg (S) / Dual Leg (D) SRL Class	Working Length (ft.)	Lifeline Material	Lifeline Dimensions (in.)	Housing Material	Weight (lbs.)	1. Steel Snap Hook (1)	2. Steel Shivel Snap Hook (2)	3. Dielectric Snap Hook (3)	4. Steel Teck Snap Hook (4)	5. Steel Swivel Rear Hook (5)	6. Steel Swivel Rear Hook (6)	7. Steel Swivel Rear Hook (7)	8. Steel Swivel Rear Hook (8)	9. Steel Swivel Rear Hook (9)	10. Steel Swivel Rear Hook (10)	11. Steel Swivel Rear Hook (11)	12. Steel Swivel Rear Hook (12)	13. Steel Swivel Rear Hook (13)	14. Steel Swivel Rear Hook (14)	15. Steel Swivel Rear Hook (15)	16. Steel Swivel Rear Hook (16)	17. Steel Swivel Rear Hook (17)	18. Steel Swivel Rear Hook (18)	19. Steel Swivel Rear Hook (19)	20. Steel Swivel Rear Hook (20)	21. Steel Swivel Rear Hook (21)	22. Steel Swivel Rear Hook (22)
024-5434	1 S	11	Dyneema® Webbing	.7X.05	Clear Resin	2.6	X											X										
024-5435	1 S	11	Dyneema® Webbing	.7X.05	Clear Resin	2.2			X									X										
024-5436	1 S	11	Dyneema® Webbing	.7X.05	Clear Resin	3.4						X						X										
024-5437	1 S	11	Dyneema® Webbing	.7X.05	Clear Resin	3.2									X			X										
024-5438	1 S	11	Dyneema® Webbing	.7X.05	Clear Resin	3.0	X											X										
024-5439	1 S	11	Dyneema® Webbing	.7X.05	Clear Resin	2.6			X									X										
024-5440	1 S	11	Dyneema® Webbing	.7X.05	Clear Resin	3.8						X						X										
024-5441	1 S	11	Dyneema® Webbing	.7X.05	Clear Resin	3.6								X				X										
024-5442	1 S	11	Dyneema® Webbing	.7X.05	Clear Resin	3.1	X											X										
024-5443	1 S	11	Dyneema® Webbing	.7X.05	Clear Resin	2.7			X									X										
024-5444	1 S	11	Dyneema® Webbing	.7X.05	Clear Resin	3.9						X						X										
024-5445	1 S	11	Dyneema® Webbing	.7X.05	Clear Resin	3.7								X				X										
024-5446	1 S	11	Dyneema® Webbing	.7X.05	Clear Resin	2.9	X											X										
024-5447	1 S	11	Dyneema® Webbing	.7X.05	Clear Resin	2.5			X									X										
024-5448	1 S	11	Dyneema® Webbing	.7X.05	Clear Resin	3.7						X						X										
024-5449	1 S	11	Dyneema® Webbing	.7X.05	Clear Resin	3.5								X				X										
024-5450	1 D	11	Dyneema® Webbing	.7X.05	Clear Resin	6.0	X											X			X							
024-5451	1 D	11	Dyneema® Webbing	.7X.05	Clear Resin	5.2			X									X			X							
024-5452	1 D	11	Dyneema® Webbing	.7X.05	Clear Resin	7.6						X						X			X							
024-5453	1 D	11	Dyneema® Webbing	.7X.05	Clear Resin	7.2								X				X			X							
024-5454	1 D	11	Dyneema® Webbing	.7X.05	Clear Resin	5.6	X																					X
024-5455	1 D	11	Dyneema® Webbing	.7X.05	Clear Resin	4.8			X																			X
024-5456	1 D	11	Dyneema® Webbing	.7X.05	Clear Resin	7.2						X																X
024-5457	1 D	11	Dyneema® Webbing	.7X.05	Clear Resin	6.8								X														X
024-5458	1 D	11	Dyneema® Webbing	.7X.05	Clear Resin	5.7	X																				X	
024-5459	1 D	11	Dyneema® Webbing	.7X.05	Clear Resin	4.9			X																		X	
024-5460	1 D	11	Dyneema® Webbing	.7X.05	Clear Resin	7.3						X															X	
024-5461	1 D	11	Dyneema® Webbing	.7X.05	Clear Resin	6.9								X													X	

