



## Lodestar Lift Cable SRL

\*See chart for part numbers, hook configurations, and product weights

### FEATURES :

- Durable stainless steel housing with nylon sides
- Framless design creates thinner housing size
- Side payout for smooth retraction
- Compact shockpack
- RFID equipped
- 360/180° attachment point swivels for full range of motion
- Designed for sharp leading edges with foot-level connection
- Single leg leg options available
- Warning tag on top of housing to denote anchor connection
- Available with various hook options, see chart
- All components are Z359.12 compliant
- \*\*\*Not an SRL-P\*\*\*



Class

**2**

Anchor above or below dorsal D-ring

Product shown:  
024-5479

### USER WEIGHT CAPACITY

|      |                          |
|------|--------------------------|
| ANSI | 130-310 lbs. (59-141 kg) |
| OSHA | Up to 420 lbs. (191 kg)  |

### STANDARD COMPLIANT WITH

|      |                   |
|------|-------------------|
| ANSI | Z359.14-2021      |
| OSHA | 1910.140, 1910.66 |

### ANSI CLASS 1

|                                                        |                       |
|--------------------------------------------------------|-----------------------|
| Max. arrest force                                      | ≤ 1,800 lbs. (817 kg) |
| Avg. arrest force                                      | ≤ 1,350 lbs. (612 kg) |
| Max. arrest distance                                   | ≤ 42 in. (107 cm)     |
| Actual arrest distance                                 | ≤ 21 in. (53 cm)      |
| Max. free fall distance                                | 24 in. (61 cm)        |
| Min. required fall clearance                           | 5 ft. 3 in. (1.6 m)   |
| For full clearance requirements, see user instructions |                       |

### ANSI CLASS 2

|                                                        |                       |
|--------------------------------------------------------|-----------------------|
| Max. arrest force                                      | ≤ 1,800 lbs. (817 kg) |
| Avg. arrest force                                      | ≤ 1,350 lbs. (612 kg) |
| Max. arrest distance                                   | N/A                   |
| Actual arrest distance                                 | ≤ 105 in (267 cm)     |
| Max. free fall distance                                | 72 in. (183 cm)       |
| Min. required fall clearance                           | 17 ft. 3 in. (5.3 m)  |
| For full clearance requirements, see user instructions |                       |

### MATERIAL SPECIFICATION

|              |                                                 |
|--------------|-------------------------------------------------|
| Cable        | 3/16" galvanized Steel Cable                    |
| Carabiner    | YCM plated steel                                |
| Housing      | Stainless steel and nylon                       |
| Hook options | Steel and aluminum (dependent on configuration) |
| Shock pack   | Polyester and tarpaulin                         |



# SAFEWAZE

## TECHNICAL DATA SHEET

### Lodestar Lift Cable SRL

# LODESTAR

LIFT

Standards: ANSI Z359.14-2021  
OSHA 1910.140 & 1910.66

Capacity: ANSI 130-310 lbs. (59-141 kg)  
OSHA Up to 420 lbs. (191kg)

#### CONNECTOR

#### ATTACHMENT

| Part Number | Single Leg (S) / Dual Leg (D) | Working Length (ft.) | Lifeline Material | Lifeline Dimensions (in.) | Housing Material | Weight (lbs.) | LI Steel Swivel Snap Hook ① | LI Steel Snap Hook ② | Dielectric Snap Hook ③ | Steel Tie Back Hook ④ | Steel Rebar Hook ⑤ | LI Steel Swivel Rebar Hook ⑥ | Steel Swivel Rebar Hook ⑦ | Steel Captive Eye Hook ⑧ | ALU Captive Eye Carabiner ⑨ | ALU Swivel Carabiner ⑩ | Tripp Lock Steel Carabiner ⑪ | No Attachment ⑫ | Steel Carabiner ⑬ | ALU Captive Eye Carabiner ⑭ | ALU Carabiner ⑮ | ALU Snap Hook ⑯ | Cab Mount Bracket ⑰ | ES-EX313 ⑱ | Integrated BWS ⑲ | Soft Loop ⑳ | 1014 BWS ㉑ | 9012 BWS ㉒ | 9013 BWS ㉓ |
|-------------|-------------------------------|----------------------|-------------------|---------------------------|------------------|---------------|-----------------------------|----------------------|------------------------|-----------------------|--------------------|------------------------------|---------------------------|--------------------------|-----------------------------|------------------------|------------------------------|-----------------|-------------------|-----------------------------|-----------------|-----------------|---------------------|------------|------------------|-------------|------------|------------|------------|
| 024-5479    | 2                             | S                    | 9                 | Steel Cable               | Ø3/16            | Nylon/SS      | 4.4                         | X                    |                        |                       |                    |                              |                           |                          |                             |                        |                              |                 | X                 |                             |                 |                 |                     |            |                  |             |            |            |            |
| 024-5480    | 2                             | S                    | 9                 | Steel Cable               | Ø3/16            | Nylon/SS      | 4.0                         |                      | X                      |                       |                    |                              |                           |                          |                             |                        |                              |                 | X                 |                             |                 |                 |                     |            |                  |             |            |            |            |
| 024-5481    | 2                             | S                    | 9                 | Steel Cable               | Ø3/16            | Nylon/SS      | 4.0                         |                      |                        |                       |                    |                              |                           |                          |                             |                        | X                            |                 | X                 |                             |                 |                 |                     |            |                  |             |            |            |            |

