



DECLARATION OF CONFORMITY

DECLARATION DATE: 4/22/25	DECLARATION #: SW25DC028
TEST REPORT #(S): L24110101, 250414060	TEST LAB(S): Yoke

ITEM TESTED	DESCRIPTION
024-5450	Latitude Pro 11' Dual Web SRL: FS-EX313, Carabiner, Snap Hooks

ADDITIONAL ITEMS CONFORMING UNDER THIS DECLARATION

024-5451, 024-5452, 024-5453, 024-5454, 024-5455, 024-5456, 024-5457, 024-5458, 024-5459, 024-5460, 024-5461

Safewaze declares that the product(s) listed above is in conformity with the requirements of the following standard(s) and/or regulation(s).

ANSI Z359.14-2021 / OSHA 1910.140, 1910.66

ABOVE D-RING USE	STANDARD	ANSI CLASS 1, OSHA up to 420 lbs.	BELOW D-RING USE	STANDARD	OSHA 130-310 lbs.
	Max Arrest Force	≤ 1800 lbs. (816.47 kg)		Max Arrest Force	≤ 1800 lbs. (816.47 kg)
	Average Arrest Force	≤ 1350 lbs. (612.35 kg)		Average Arrest Force	≤ 900 lbs. (408.23 kg)
	Max Arrest Distance	≤ 42 in. (106.68 cm)			
	Actual Arrest Distance	≤ 39.37 in. (100.00 cm)		Actual Arrest Distance	≤ 53.1 in. (134.88 cm)
	Use Below D-ring	Not permitted		Use Below D-ring	2 ft. (0.61m)
	Max Free Fall Distance	24 in. (60.96 cm)		Max Free Fall Distance	24 in. (60.96 cm)

CONFORMITY ASSESSMENT METHOD

LEVEL 1: Safewaze lab or Independent 3rd Party outside the scope of ISO 17025:2005	
LEVEL 2: Safewaze lab within the scope of ISO 17025:2005	
LEVEL 3: Independent 3rd Party accredited to ISO 17025:2005	X

This certificate is a guarantee that the above standard(s) and/or regulation(s) was met by all requirements. Testing was conducted under normal operation mode. The results of testing apply only to the particular sample tested and to the specific test carried out. This Certificate is only issued for products which have passed the requirements listed in the standard(s) and/or regulation(s).

TITLE: Testing Director
NAME: Chad Hilliard
SIGNATURE: 

Last Edit: 6/4/25