



025-4130

Purlin Anchor

FEATURES :

- Temporary or permanent anchor for installation on 12-16 gauge C and Z purlins
- Replaceable captive eye connection (026-4144) in case of anchor wear
- NBR foam gasket on the bottom of the captive eye creates a water tight seal on the roof
- Captive eye intentionally deforms in a fall event to absorb energy and reduce forces on the roof structure and user.
- Can be used in both upright and overhead orientations
- HLL use only permitted in upright orientation
- 1 user maximum
- Not for Material Hauling
- Minimum Breaking Strength: 5,000 lbs. (22 kN)
- Dimensions: 14.25" x 5.75" x 4.25" (36.2 cm x 14.6 cm x 10.8 cm)

ATTACHMENT POINT(S) :

- 1 Captive eye

ITEM WEIGHT :

- 7.4 lbs. (3.4 kg)



USER WEIGHT CAPACITY

ANSI	130-310 lbs. (59-141 kg)
OSHA	Up to 420 lbs. (191 kg)

STANDARD COMPLIANT WITH

ANSI	N/A
OSHA	1926.502, 1910.140, 1910.66

COMPATIBLE COMPONENTS

026-4144	Purlin Anchor Captive Eye Replacement

COMPONENT

MATERIAL SPECIFICATION

Anchor	Zinc-plated steel
Gasket	NBR foam
Fasteners	Zinc-plated steel