SAFEWAZE

TECHNICAL DATA SHEET

025-4135

Rail Anchor

FEATURES:

- Designed for temporary installation on existing approved rails
- Quick installation using interlocking twin plate design
- Compact and lightweight with enhanced user-trailing mobility
- Double-plated steel with Hi-vis green powder coating and reflective label to increase visibility and durability
- Anchor fits rails ranging from 90-141 lbs./yd. with head widths between 2.72”-3.07”
- Designed to be used with a leading edge lanyard or SRL
- Dimensions: 3.5” X 5.7” X 4.2” w/o Carabiner
- Includes a 5K-rated carabiner for secure attachment of lanyards and SRL hooks. Replacement carabiners sold separately.

ATTACHMENT POINTS:

- 5K Gate Carabiner

MINIMUM BREAKING STRENGTH:

- 3,600 lbs. (16 kN)

ITEM WEIGHT:

- 4.8 lbs. (2.2 kg) with Carabiner





USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-141 kg)
OSHA	Up to 420 lbs. (191 kg)

STANDARD COMPLIANT WITH	
ANSI	N/A
OSHA	1926.502, 1910.140, & 1910.66

Related Item(s)	
026-9122	Steel Carabiner w/ 5K Gate (Black)

COMPONENT	MATERIAL SPECIFICATION
Anchor	Powder coated, plated steel
Carabiner	EP coated steel