SAFEWAZE

NEW PRODUCT SPOTLIGHT



RAIL ANCHOR

BUILT FOR MOBILITY. FAST TO INSTALL.

025-4135

- **Engineered for dependable, smooth operation with enhanced user trailing.**
- **Simple attachment with a unique interlocking twin plate design for easy installation to save time.**
- **Increased safety with hi-vis green powder coating and reflective label for extra visibility.**
- **Constructed for extreme durability in tough rail yard environments.**



025-4135

RAIL-READY PROTECTION

DEPENDABLE OPERATION



QUICK, EASY INSTALLATION



HIGH VISIBILITY



ADDED DURABILITY





ADDITIONAL FEATURES:

» Temporary anchor, reusable on approved rails
» Lightweight, compact design for easy portability
» Engineered for compliant use at foot-level tie off
» Use with Class 2 SRLs and leading edge lanyards
» Includes 5K-rated carabiner for secure attachment

SKU	DESCRIPTION
025-4135	Rail Anchor
026-9122	Replacement Carabiner

KEY SPECS:
Materials: Double-plated, powder-coated steel
Dimensions: 3.5” x 5.7” x 4.2” (8.9 cm x 14.5 cm x 10.7 cm) not including carabiner
Rail Compatibility: 90–141 lbs./yd.
Head Width: 2.72”–3.07” (6.9–7.8 cm)
Minimum Breaking Strength: 3,600 lbs.
Item Weight: 4.8 lbs. (2.2 kg) with carabiner
OSHA Standards: 1926.502, 1910.140, 1910.66